

COLOUR TEMP. (K)		LAMP (W)	VOLTAGE (V)
3200	FILL	1000	230 240
TUNGSTEN		HALOGEN	AVAILABLE

## Cosmobroad 1000 W with barndoor and safety mesh

The Cosmobroad is a 1000 W, open-face, tungsten-halogen floodlight, which provides an extremely soft, wide and even illumination. Particularly suitable for backgrounds, virtual sets, and set design.

The version with the asymmetric reflector is used as a cyclorama light.



### Main Features



- Die-cast magnesium and fiberglass housing
- Very strong and lightweight materials
- Special design and treatments of the reflector for an extremely powerful and bright light output to deliver an exceptional even illumination
- 100 % pure silver lamp contacts unique feature to extend lamp and contacts-life and reduce maintenance costs
- Silicone cable for high flexibility and to avoid fire risk
- Top quality switch with a very high number of on/off cycles
- All main mechanical components are stainless steel
- The ergonomic knob to fix the tilt position is shaped to ensure ideal handling to quickly and effortlessly fix the tilt position
- Supplied complete with safety mesh and four-leaf barndoor with gel filter clips
- **Designed and manufactured in ITALY**

### Ordering Codes

RC 110 - Cosmobroad 1000 W with barndoor and safety mesh

RC 110A - Cosmobroad 1000 W with asymmetric reflector, barndoor and safety mesh

- Die-cast magnesium and fiberglass housing
- High-temperature coating (die-cast parts only)
- Sanded and treated aluminium reflector
- Aluminium yoke mounting with 16 mm (5/8") socket
- 100 % pure silver lamp contacts
- 3.5 m VDE fire resistant silicone cable, 3 x 1.5 mm<sup>2</sup> section
- In-line 10 A switch protected by high impact-proof-housing
- Supply voltage 230 – 240 V
- Lamp base R7s
- Colour temperature 3200 K
- IP 20
- CE compliant
- Weight 2.3 kg
- Packing dimensions 270 mm x 210 mm x 170 mm



## Photometrics

1000 W

### Flood (90°)

Distance (m)	3	4	5
Lux	2100	1150	800

Typical performance based on P2/20 1000 W 230 V lamp

## Lamps \*

BASE R7s - 3200 K

CODE	WATT	ANSI	LIF
RC 110 	1000-230 V	-	P2/20

OSR 64583 - OSRAM halogen lamp, P2/20 1000 W 230 V R7s  
\*not included

## Accessories



**RC 112C**  
Four-leaf barndoor  
with safety mesh  
and gel filter clips  
650 g



**RC 111**  
Safety mesh 70 g



**RC 211B**  
Aluminium stand,  
3 risers, 78/240  
cm, 16 mm spigot,  
black, 5 kg load



**RC 212B**  
Aluminium  
stand, 3 risers,  
90/280 cm, 16  
mm spigot,  
black, 5 kg load

Technical specifications and data are provided for guidance only. Due to improvement in technology and/or in products, all product, specs and data are subject to change without notice. COSMOLIGHT accepts no liability for any errors, inaccuracies or incompleteness contained herein.