

## Specifications

# Aluminium master stand - 124/366 cm

4 sections-3 risers stand, 1004BAC stands connect to each other for easy transportation. Air cushioning protects fingers and mounted equipment, spigot with 3/8" thread, supplied with removable 1/4-20" thread.

Wide footprint 106 cm for great stability.

Payload up to 9 kg.

Max payload	9 kg
Top attachment	1/4 screw, 3/8 screw, 5/8 (16 mm)
Max height	366 cm
Weight	2.57 kg
Arm tube diameters	35, 30, 25, 20 mm   1 3/8 - 1 3/16 - 63/64 - 25/32
Closed length	107 cm
Footprint max diameter	106 cm
Leg sections	4
Material	Aluminium, black
Min height	124 cm
Section centre column	4 sections, 3 risers



## Ordering Codes

1004BAC - Aluminium stand, 3 risers, 124/366 cm, air cushioned, 16 mm spigot, black, 9 kg load



## Specifications

## Aluminium master stand - 118/273 cm

3 sections-2 risers stand with a payload of up to 10Kg  
 1005BAC stands connect to each other for easy transportation Air cushioning protects fingers and mounted equipment Removable reversible spigot w/ 1/4" and 3/8" thread.  
 Payload up to 10 kg.

Max payload	10 kg
Top attachment	1/4 screw, 3/8 screw, 5/8 (16 mm)
Max height	273 cm
Weight	2.5 kg
Arm tube diameters	35, 30, 25 mm   1 3/8 - 1 3/16 - 63/64
Closed length	100 cm
Footprint max diameter	106 cm
Leg sections	3
Material	Aluminium, black
Min height	118 cm
Section centre column	3 sections, 2 risers



## Ordering Codes

1005BAC - Aluminium stand, 2 risers, 118/273 cm, air cushioned, 16 mm socket, black, 10 kg load



Technical specifications and data are provided for guidance only. Due to improvement in technology and/or in products, all product, specs and data are subject to change without notice. COSMOLIGHT accepts no liability for any errors, inaccuracies or incompleteness contained herein.