

Specifications

Aluminium stand - 110/198 cm

3 sections-2 risers stand and 1 levelling leg.

Max payload	25 kg
Attachment 01	1 1/8 (28 mm) bushing not threaded
Attachment 02	5/8 (16 mm) spigot not threaded
Attachment number	1 1/8 female & 5/8 male attachment type
Max height	198 cm
Weight	4.5 kg
Arm tube diameters	45, 40, 35 mm
Closed length	93 cm
Material	Aluminium, black
Min height	110 cm
Section centre column	3 sections, 2 risers

Ordering Codes

A1020B - Aluminium stand, 2 risers, 110/198 cm, 28/16 mm socket, black, 25 kg load



Aluminium stand - 168/350 cm

4 sections-3 risers stand and 1 levelling leg.

Max payload	30 kg
Attachment 01	1 1/8 (28 mm) bushing not threaded
Attachment 02	5/8 (16 mm) spigot not threaded
Attachment number	1 1/8 female & 5/8 male attachment type
Max height	350 cm
Weight	7 kg
Arm tube diameters	45, 40, 35 mm
Closed length	42 cm
Material	Aluminium, black
Min height	168 cm
Section centre column	3 sections, 2 risers

Ordering Codes

A1035B - Aluminium stand, 2 risers, 168/350 cm, 28/16 mm socket, black, 30 kg load



Specifications

Aluminium stand - 179/450 cm

4 sections-3 risers stand and 1 levelling leg.

Max payload	30 kg
Attachment 01	1 1/8 (28 mm) bushing not threaded
Attachment 02	5/8 (16 mm) spigot not threaded
Attachment number	1 1/8 female & 5/8 male attachment type
Max height	450 cm
Weight	7.7 kg
Arm tube diameters	45, 40, 35, 30 mm - 25 mm leg
Closed length	155 cm
Material	Aluminium, black
Min height	179 cm
Section centre column	4 sections, 3 risers

Ordering Codes

A1045B - Aluminium stand, 2 risers, 179/450 cm, 28/16 mm socket, black, 30 kg load

