

## Specifications

### Aluminium stand - 78/240 cm

4 sections-3 risers stand with a payload of up to 5 Kg, 16 mm spigot, black.  
Excellent protection against corrosion and wear is ensured by aluminium anodisation.

Max payload	5 kg
Top attachment	16 mm spigot
Max height	240 cm
Weight	1 kg
Arm tube diameters	25, 22, 19, 16 mm – 19 mm leg
Closed length	67 cm
Footprint max diameter	94 cm
Leg sections	4
Material	Aluminium
Min height	78 cm
Section centre column	4 sections, 3 risers



#### Ordering Codes

RC 211B - Aluminium stand, 3 risers, 78/240 cm, 16 mm spigot, black, 5 kg load

### Aluminium stand - 90/280 cm

4 sections-3 risers stand with a payload of up to 5 Kg, 16 mm spigot, black.  
Excellent protection against corrosion and wear is ensured by aluminium anodisation.

Max payload	5 kg
Top attachment	16 mm spigot
Max height	280 cm
Weight	1.1 kg
Arm tube diameters	25, 22, 19, 16 mm – 19 mm leg
Closed length	76 cm
Footprint max diameter	94 cm
Leg sections	4
Material	Aluminium, black
Min height	90 cm
Section centre column	4 sections, 3 risers



#### Ordering Codes

RC 212B - Aluminium stand, 3 risers, 90/280 cm, 16 mm spigot, black, 5 kg load

Technical specifications and data are provided for guidance only. Due to improvement in technology and/or in products, all product, specs and data are subject to change without notice. COSMOLIGHT accepts no liability for any errors, inaccuracies or incompleteness contained herein.