

SM Select Control



Control panel to operate IFF Hoists in theaters, auditoriums and studios.

The SM Select Control panel allows the operator to select multiple hoists and operate groups via the up/down push button on the control panel or on the pendant push control. The SM control is furnished with a key switch to prevent unauthorized access and an Emergency Stop Button. Together with the ASM power panel the SM control is a very efficient and safe way to control hoists.

Model Range

Code		Enclosure H x W x D
FF3951Y002UR	controls 2 hoists	306x256x150 12"x 10"x 5.9"
FF3951Y004UR	controls 4 hoists	306x256x150 12"x 10"x 5.9"
FF3951Y006UR	controls 6 hoists	306x256x200 12"x10"x7.9"
FF3951Y010UR	controls 10 hoists	500x400x200 19.7"x15.7"x7.9"
FF3951Y012UR	controls 12 hoists	500x400x200 19.7"x15.7"x7.9"
FF3951Y018UR	controls 18 hoists	500x400x200 19.7"x15.7"x7.9"
FF3951Y024UR	controls 24 hoists	600x400x200 23.6"x15.5"X7.9"
FF3951Y030UR	controls 30 hoists	600x400x200 23.6"x15.5"X7.9"
FF3951Y036UR	controls 36 hoists	600x400x200 23.6"x15.5"X7.9"

Technical Features

Electrical connection

Voltage	220VAC	120VAC
Current	1A	1A

Control signal

Up/down	+/- 24VDC
E-stop	Normally closed contact for 24V . The E-stop must be connected to the ASM power panel to ensure a proper function of the E-stop. Please contact IFF if the SM control panel is used without ASM power panel.

Pendent control

Cord	25m	75'
Up/down push button		
E-stop button		

