## Aluminium stand - 78/240 cm

RC 211B - 4 sections, 3 risers stand with a payload of up to 5 Kg, 16 mm spigot, black. Excellent protection against corrosion and wear is ensured by aluminium anodisation.

Max payload 5 kg


Top attachment 16 mm spigot Max height 240 cm Weight 1 kg

25, 22, 19, 16 mm - 19 mm leg Arm tube diameters

Closed length 67 cm Footprint max diameter 994 cm Leg sections

Material Aluminium Min height 78 cm

Section centre column 4 sections, 3 risers



RC 211B - Aluminium stand, 3 risers, 78/240 cm, 16 mm spigot, black, 5 kg load

## Aluminium stand - 90/280 cm

RC 212B - 4 sections, 3 risers stand with a payload of up to 5 Kg, 16 mm spigot, black. Excellent protection against corrosion and wear is ensured by aluminium anodisation.

Max payload 5 kg

16 mm spigot Top attachment 280 cm Max height Weight 1.1 kg

25, 22, 19, 16 mm - 19 mm leg Arm tube diameters

76 cm Closed length 994 cm Footprint max diameter Leg sections

Material Aluminium, black

90 cm Min height

Section centre column 4 sections, 3 risers

## **Ordering Codes**

RC 212B - Aluminium stand, 3 risers, 90/280 cm, 16 mm spigot, black, 5 kg load

